## **Concatenating Data**

In this example we will loop through files containing each a year of data. We will then concatenate the data either along the time dimension (to compute the time average) or along a new dimension in order to compute statitistic between years (standard deviation, etc..)

```
import cdms, MV, genutil
import sys
pth=sys.prefix+'/sample_data/'
files = [ pth+'u_2000.nc',
           pth+'u_2001.nc',
           pth+'u_2002.nc',
for file in files:
    f=cdms.open(file)
\hat{A} \hat{A} \hat{A} \hat{A} u=f('u')
\hat{A} \hat{A} \hat{A} if file == files[0]: # First file \hat{A} \hat{A} \hat{A} sh=list(u.shape) # Create a 1.
                                         # Create a list with the shape of the data
\hat{A} \hat{A} \hat{A} \hat{A} \hat{A} \hat{A} \hat{A} \hat{A} sh.insert(0,1)
                                              # Insert value 1 in front of the list
\hat{A} \hat{A} \hat{A} \hat{A} \hat{A} \hat{A} newdim = MV.reshape(u,sh) # Create a new 1D dimension
         \# add u at the end of accumaltion on dimension 0
         accumulation = MV.concatenate((accumulation, u))
\hat{A} \hat{A} \hat{A} \hat{A} \hat{A} \hat{A} \hat{A} tmp = MV.reshape(u,sh) # Create a new 1D dimension
\hat{A} \hat{A} \hat{A} \hat{A} \hat{A} \hat{A} \hat{A} \hat{A} newdim = MV.concatenate((newdim,tmp)) # Add u to the newdim over the new dimension
\hat{A} \hat{A} \hat{A} f.close()
print newdim.shape # Has a new dimension for years
avg = MV.average(accumulation)
std = genutil.statistics.std(newdim)
print avg.shape
print std.shape
```